


NOTES:

1. ENSURE SUBSOIL DRAINS TOWARDS PERFORATED DRAIN TILE.
2. INSTALL PERFORATED DRAIN TILE AT 16' (4.8m) ON CENTER AS WELL AS AROUND THE PERIMETER OF THE SofTILE INSTLATION. DRAIN TO NEAREST STORM COLLECTION SYSTEM.
3. BACK FILL AROUND PERFORATED DRAIN TILE WITH $\frac{3}{4}$ " (20mm) CLEAR STONE TO 6" (150mm) RADIUS AROUND TILE.
4. WRAP WITH Geotextile Terrafox 200R TO PERVENT CLOGGING.

THICKNESS	CRITICAL FALL HEIGHT (FT)		REVISIONS			
	WITH 10 YEAR PERFORMANCE WARRANTY	WITH 10 YEAR PERFORMANCE WARRANTY	REV	DESCRIPTION	DATE	APPR
	PLUS SERIES	PREMIUM SERIES (EPDM)				
1.75"	3.0	3.0	0	ORIGINAL ISSUE	8/31/04	
2.00"	4.0	4.0	1	UPDATED	10/21/04	
2.25"	5.0	5.0	2	UPDATED	02/02/06	
2.50"	6.0	6.0				
2.75"	7.0	7.0				
3.25"	8.0	8.0				
3.50"	9.0	9.0				
3.75"	10.0	10.0				

FILE NAME: A0001SK14 PREPARED BY: B.GOSS SCALE: A FSCM NO.: DWG NO.: 2000-001 REV: 2
 NTS SHEET: SK14



SAFETY SURFACE (RESILIENT TILE - Concrete Edge)

The Maryland-National Capital Park and Planning Commission
Montgomery County Department of Parks

Detail No.

SEPT. 2008